



Glazed Vitrified Tiles

600x1200 mm | Matte Finish


600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles



8001



600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles



8002




600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles

8003



600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles



8004



SLIP
RESISTANT



FROST
FREE



INDOOR
USE




HD
PRINTING

600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles

8005



SLIP
RESISTANT



FROST
FREE



INDOOR
USE



HD
PRINTING


600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles



8006




600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles



8007





600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles

8008



SLIP
RESISTANT



FROST
FREE



INDOOR
USE



HD
PRINTING


600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles



8009




600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles

8010



SLIP
RESISTANT



FROST
FREE



INDOOR
USE



HD
PRINTING



600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles



8011



600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles

8012



SLIP
RESISTANT



FROST
FREE



INDOOR
USE



HD
PRINTING


600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles



8013



600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles



8014



SLIP
RESISTANT



FROST
FREE



INDOOR
USE



HD
PRINTING

600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles



8015



SLIP
RESISTANT

FROST
FREE

INDOOR
USE

HD
PRINTING

600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles



8016



600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles



8017



600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles



8018



600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles

8019



600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles

8020



SLIP
RESISTANT

FROST
FREE

INDOOR
USE

HD
PRINTING

600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles



8021



600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles



8022



600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles



8023



600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles



8024



600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles



8025




600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles



8026



600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles



8027



600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles



8028





600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles



8029



600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles



8030



600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles



8031



600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles



8032




600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles



8033



SLIP
RESISTANT



FROST
FREE



INDOOR
USE



HD
PRINTING

600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles



8034






600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles



8035




600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles



8036



600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles



8037



600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles



8038



SLIP
RESISTANT



FROST
FREE



INDOOR
USE



HD
PRINTING

600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles



8039




600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles



8040



600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles



8041



600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles



8042



600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles



8043



600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles



8044



600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles

8045



600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles



8046




600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles



8047




600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles



8048



SLIP
RESISTANT



FROST
FREE



INDOOR
USE



HD
PRINTING

600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles

8049



SLIP
RESISTANT



FROST
FREE



INDOOR
USE



HD
PRINTING

600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles



8050



600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles

8051




600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles



8052



SLIP
RESISTANT



FROST
FREE



INDOOR
USE



HD
PRINTING

600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles

8053



SLIP
RESISTANT



FROST
FREE



INDOOR
USE



HD
PRINTING

600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles



8054



600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles



8055




600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles



8056



600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles



8057



600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles



8058



600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles



8059




600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles



8060



600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles



8061



SLIP
RESISTANT

FROST
FREE

INDOOR
USE

HD
PRINTING


600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles



8062



600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles



8063



600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles

8064



SLIP
RESISTANT



FROST
FREE



INDOOR
USE



HD
PRINTING

600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles



8065



600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles



8066




600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles

8067



600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles



8068



600x1200 mm

MATTE FINISH

Glazed Vitrified Tiles



8069



TECHNICAL SPECIFICATIONS

Glazed Vitrified Tiles

Packing Details			
Size	No. of Tiles Per Carton	Covered Area Per Carton	
(In mm.)		(In Sq. Mtr.)	(In Sq. Ft.)
600X1200	2	1.44	15.5

Group B Ia as per ISO 13006:2012 and Group B Ib as per IS 15622:2017					
Characteristics	Test Methods	Requirement as per ISO 13006 ≤ 0.5 Group B Ia	Requirement as per IS 15622:2017 0.08<E ≤ 3% Group B Ib		OBL Norms
Dimension & Surface Quality	IS 13630 (Part 1):2006		Unrectified	Rectified	
Deviation in Length & Width		±0.6%	± 0.4%	± 0.1 %	± 0.1 %
Deviation in Thickness		±5%	± 5.0 %		± 4 %
Straightness of Sides		±0.5%	± 0.3 %	± 0.1 %	± 0.1 %
Rectangularity		±0.5%	± 0.3 %	± 0.1 %	± 0.1 %
Surface Flatness		±0.5%	± 0.5 %		± 0.2 % 😊😊
Surface Quality		Min. 95 % tiles should be free from visible defects	Min. 95 % tiles should be free from visible defects		Conforms
Physical Properties					
Water Absorption	IS 13630 (Part 2):2006	Avg 0.08<E ≤ 3, Individual 3.3, Max	Avg 0.08<E ≤ 3, Individual max, 3.3		Avg ≤ 0.5, Individual max, 0.6 😊
Modulus of Rupture in [N/mm ²]	IS 13630 (Part 6):2006	Minimum 35, Individual 32, Min	Avg 30, Individual 27, Min		Avg 38 Min, Individual 35, Min 😊
Breaking Strength in N	IS 13630 (Part 6):2006	< 7.5 mm thickness: 700, Min ≥ 7.5 mm thickness: 1300, Min	< 7.5 mm thickness: 700, Min ≥ 7.5 mm thickness: 1100, Min		1500 Min 😊
Moisture Expansion in mm/m	IS 13630 (Part 3):2006	Declare Value	0.02, Max		< 0.02
Scratch Hardness of Surface (Moh's Scale)	IS 13630 (Part 13):2006	NA	5, Min		5 to 8 Depending on Design/Surface 😊😊
Resistance to Surface Abrasion of glazed tiles (Class I to V)	IS 13630 (Part 11):2006	Test Method Available	Class II, Min		Class-III to Class-V Depending as per Design / Surface 😊
Co-efficient of Linear Thermal Expansion from ambient temperature to 100°C	IS 13630 (Part 4):2006	Test Method Available	7×10 ⁻⁶ K ⁻¹ , Max		Conforms
Thermal Shock Resistance	IS 13630 (Part 5):2006	Test Method Available	10 cycles, Min		Passed
Crazing Resistance	IS 13630 (Part 9):2006	Test Method Available	4 Cycles@7.5 bar, Min		4 Cycle @ 7.5 Bar Min 😊😊
Frost Resistance	IS 13630 (Part 10):2006	Required	Required		Resistance
Bulk Density, in (g/cc)	IS 13630 (Part 12):2006	NA	2.0, Min		> 2.1
Impact resistance- Coefficient of restitution	IS 13630 (Part 14):2006	Manufacturer to State	0.55, Min		0.7-0.85
Chemical Properties					
Resistance to staining of glazed tiles	IS 13630 (Part 8):2006	Min, Class 3	Class I, Min		Conforms
Resistance to household chemicals		Min, GA	Class AA, Min		Conforms
Resistance to acids and alkalis (with exception of hydrofluoric acid and its compounds)		Test Method Available	Required, if agreed		Conforms

NOTE: Certain amount of Size and Shade variation is inherent in all ceramic products. Within the limits of printed material, the colors and aesthetics of the products correspond closely to those of illustrated products. Prospective customers are advised to inspect a sample of the tile before ordering and laying. At all points of time, the company liability is restricted to the purchase value of tiles.

Every effort has been made to ensure the accuracy of the information given. However, the company reserves the right to delete & change, any of the items, colors, sizes & technical specifications without any prior notice.



Making Tile Selection Easier



Find tiles similar to a reference image



Tiles selected by you in your room



Visualise selected tiles & get a quote



Share layout for a personalised render*

www.orientbell.com

CORPORATE OFFICE:

Iris House, 16 Business Centre,
Nangal Raya, New Delhi-110046, India
Tel: +91-11-47119100, Fax: +91 -11-2852 1273

REGISTERED OFFICE:


8 Industrial Area, Sikandrabad-203 205 (UP), India
Tel: +91-5735-222-203 / 24, +91-8191004575/ 76
Fax: +91 -5735 222 642

CUSTOMER CARE:

customercare@orientbell.com
Call : +91 87507 11111
Whatsapp : +91 87507 33333

CIN: L14101UP1977PLC021546

Please join us on social media



www.orientbell.com

