

Fusion Series

60x120 | 60x60 CM



About OBL

Orient Bell Limited (OBL) is amongst the largest manufacturers of Wall and Floor Tiles. Established in 1977, OBL has been a pioneer in the Industry with a focus on customer-centric innovation.

First to manufacture ultra-vitrified tiles, new product designs & development is a continuous process at OBL. As a result it has an extensive range of tiles with various finishes & textures. It has 4 patent-pending technologies: Forever Tiles, GermFree Tiles, Cool Tiles & Life Tiles.

To display extensive range of tiles, we have a chain of signature showrooms. Privileged to be associated with premier architects and construction agencies of the country, it also counts most leading developers as well as government & public sector institutions as its customers.

- The ISO 9001:2015 accreditation for our quality control management systems reflects the quest for manufacturing international standard products.
- In 2015 our Sikandarabad plant was awarded with prestigious ISI certification for its products.
- In May 2000, OBL was awarded ISO 14001 certification by the internationally recognised BSI Management Systems, UK.
- Our manufacturing units are ISO 14001:2015 certified, the most complete and global expression for an environment friendly industrial company.
- We have been awarded OHSAS 18001 Certification for Health & Safety Standards. No waste water is ever discharged from our factory.
- We were also awarded with "Certificate Of Merit" in 'National Energy Conservation Award' 2016 organised by Ministry of Power for saving Power and Fuel consumption.

















Listed on BSE (530365) for 20+ years. And also on NSE (ORIENTBELL).

INDEX

MARBLE		HIGHLIGHTER	
60X120 CM ROCKER ANTIQUE MARBLE 60X60 CM ROCKER ANTIQUE MARBLE 60X120 CM ROCKER GRAFTON BROWN 60X60 CM ROCKER GRAFTON BROWN 60X60 CM SATIN ACCONA MARBLE BLUE 60X120 CM SATIN CALACATTA MARBLE 60X60 CM SATIN CALACATTA MARBLE 60X120 CM SATIN SOFTMARBO 60X60 CM SATIN SOFTMARBO 60X60 CM SATIN SOFTMARBO 60X120 CM SUPER GLOSS ANGELO MARBLE 60X60 CM SUPER GLOSS ONYX STONE MARBLE 60X120 CM SUPER GLOSS ONYX STONE MARBLE 60X60 CM SUPER GLOSS ONYX STONE MARBLE	01 06 01 06 06 01 06 01 05 03 03 04 04	60X120 CM DGVT ENCAUSTIC MULTI 60X60 CM DGVT ENCAUSTIC MULTI 60X120 CM DGVT GEOMETRIC NATURAL STONE-A 60X120 CM DGVT GEOMETRIC NATURAL STONE-A 60X120 CM DGVT GEOMETRIC NATURAL STONE-B 60X120 CM DGVT GEOMETRIC NATURAL STONE-B 60X120 CM DGVT MOSAIC ART DÉCOR 60X60 CM DGVT MOSAIC ART DÉCOR-A 60X60 CM DGVT MOSAIC ART DÉCOR-B 60X60 CM PGVT BLOSSOM MOSAIC 60X120 CM PGVT FLAKES MULTI 60X60 CM PGVT FLAKES MULTI 60X120 CM PGVT FLAKES MULTI MICA 60X120 CM PGVT GEOMETRIC MARBLE 60X60 CM PGVT GEOMETRIC MARBLE 60X60 CM PGVT ILLUSION ART	16 19 19 20 21 21 21 22 17 17 18 18 15 15 22
60X120 CM PGVT MOLD GREY 60X60 CM PGVT MOLD GREY 60X120 CM PGVT SPRAY GRANITE 60X60 CM PGVT SPRAY GRANITE	08 08 08 08	CEMENT	
WOOD 60X120 CM DGVT VENEER MULTI WOOD 60X60 CM DGVT VENEER MULTI WOOD 60X60 CM ROCKER BRICK WOOD 60X120 CM ROCKER BEECH WOOD 60X60 CM ROCKER BEECH WOOD	10 10 12 09	60X60 CM DGVT OPORTO BEIGE 60X60 CM ROCKER OPORTO DECOR 60X60 CM ROCKER STONE FLORA	23 23 24
TEXTURE 60X120 CM DGVT TERRAZZO BEIGE 60X60 CM DGVT TERRAZZO BEIGE 60X120 CM PGVT FORTRESS CREAMA 60X60 CM PGVT FORTRESS CREAMA	13 13 14		



Code Description

DGVT- Digital Glazed Vitrified Tiles | PGVT- Polished Glazed Vitrified Tiles

R1-No Variation | R2-Slight Variation | R3-More Variation | R4- Most Variation

F1-1 Face | F2-2 Face | F3-3 Face | F4-4 Face | F5-5 Face | F6-6 Face | F7-7 Face | F8-8 Face

G1, G2, G3, G4, G5 (Grouping) are as per technical parameters













60X120 CM | SATIN SOFTMARBO



60X120 CM | ROCKER ANTIQUE MARBLE



60X120 CM | SATIN CALACATTA MARBLE




60X120 CM | ROCKER GRAFTON BROWN




All shown tiles are Matte





60X120 CM | SUPER GLOSS ANGELO MARBLE



60X60 CM | SUPER GLOSS ANGELO MARBLE













60X60 CM | SUPER GLOSS ONYX STONE MARBLE



60X120 CM | SUPER GLOSS ONYX STONE MARBLE



60X60 CM | SATIN SOFTMARBO






Shown tile is Matte



60X60 CM | ROCKER ANTIQUE MARBLE



60X60 CM | ROCKER GRAFTON BROWN



60X60 CM | SATIN CALACATTA MARBLE




60X60 CM | SATIN ACCONA MARBLE BLUE






All shown tiles are Matte









60X120 CM | PGVT MOLD GREY



60X120 CM | PGVT SPRAY GRANITE



60X60 CM | PGVT MOLD GREY



60X60 CM | PGVT SPRAY GRANITE





60X120 CM | ROCKER BEECH WOOD



60X60 CM | ROCKER BEECH WOOD

















60X60 CM | DGVT VENEER MULTI WOOD



60X120 CM | DGVT VENEER MULTI WOOD









60X60 CM | ROCKER BRICK WOOD






60X120 CM | DGVT TERRAZZO BEIGE



60X60 CM | DGVT TERRAZZO BEIGE












60X60 CM | PGVT FORTRESS CREAMA




60X120 CM | PGVT FORTRESS CREAMA




60X120 CM | PGVT GEOMETRIC MARBLE



60X60 CM | PGVT GEOMETRIC MARBLE












60X60 CM | DGVT ENCAUSTIC MULTI



60X120 CM | DGVT ENCAUSTIC MULTI




60X120 CM | PGVT FLAKES MULTI

















60X120 CM | PGVT FLAKES MULTI MICA






60X120 CM | DGVT GEOMETRIC NATURAL STONE-A




60X60 CM | DGVT GEOMETRIC NATURAL STONE-A













60X60 CM | DGVT GEOMETRIC NATURAL STONE-B



60X120 CM | DGVT GEOMETRIC NATURAL STONE-B




60X120 CM | DGVT MOSAIC ART DÉCOR




60X60 CM | DGVT MOSAIC ART DÉCOR-A














60X60 CM | PGVT ILLUSION ART



60X60 CM | PGVT BLOSSOM MOSAIC







All shown tiles are Glossy



60X60 CM | DGVT OPORTO BEIGE



60X60 CM | ROCKER OPORTO DECOR






All shown tiles are Matte





60X60 CM | ROCKER STONE FLORA



Shown tile is Matte

TECHNICAL SPECIFICATIONS

Glazed Vitrified Tiles

Packing Details						
Size	No. of Tiles	Covered Are	Area Per Carton			
(In mm.)	No. of Tiles Per Carton	(In Sq. Mtr.)	(In Sq. ft.)			
600X1200 (SKD)	2	1.44	15.5			
600X600 (SKD)	4	1.44	15.5			

Characteristics	Test Methods	Requirement as per ISO 13006 ≤ 0.5 Group B Ia	Requirement as per IS 15622:2017 0.08 <e 3%="" b="" group="" ib<="" th="" ≤=""><th>OBL Norms</th></e>		OBL Norms
Dimension & Surface Quality			Unrectified	Rectified	
Deviation in Length & Width		±0.6%	± 0.4%	± 0.1 %	± 0.1 %
Deviation in Thickness		±5%	± 5.0 %		± 4 %
Straightness of Sides		±0.5%	± 0.3 %	± 0.1 %	± 0.1 %
Rectangularity	IS 13630 (Part 1):2006	±0.5%	± 0.3 %	± 0.1 %	± 0.1 %
Surface Flatness		±0.5%	± 0.5 % Min. 95 % tiles should be free from visible defects		± 0.2 %
Surface Quality		Min. 95 % tiles should be free from visible defects			Conforms
Physical Properties					
Water Absorption	IS 13630 (Part 2):2006	Avg ≤ 0.5, Individual max, 0.6	Avg 0.08 <e 3,="" 3.3,="" individual="" max<="" td="" ≤=""><td>Avg ≤ 0.5, Individual max, 0.6</td></e>		Avg ≤ 0.5, Individual max, 0.6
Modulus of Rupture in [N/mm²]	IS 13630 (Part 6):2006	Minimum 35, Individual 32, Min	Avg 30, Individual 27, Min		Avg 38 Min, Individual 35, Min
Breaking Strength in N	IS 13630 (Part 6):2006	< 7.5 mm thickness: 700, Min ≥ 7.5 mm thickness: 1300, Min	< 7.5 mm thickness: 700, Min ≥ 7.5 mm thickness: 1100, Min		1500, Min
Moisture Expansion in mm/m	IS 13630 (Part 3):2006	Declare Value	0.02, Max		< 0.02
Scratch Hardness of Surface (Moh's Scale)	IS 13630 (Part 13):2006	NA	5, Min		5 to 8 Depending on Design/Surface
Resistance to Surface Abrasion of Glazed Tiles (Class I to V)	IS 13630 (Part 11):2006	Test Method Available	Class II, Min		Class-III to Class-V Depending as per Design / Surface
Co-efficient of Linear Thermal Expansion from Ambiant Temperature to 100°C	IS 13630 (Part 4):2006	Test Method Available	7x10°K°1, Max		Conforms
Thermal Shock Resistance	IS 13630 (Part 5):2006	Test Method Available	10 cycles, Min		Passed
Crazing Resistance	IS 13630 (Part 9):2006	Test Method Available	4 Cycles@7.5 bar, Min		4 Cycle @ 7.5 Bar Min
Frost Resistance	IS 13630 (Part 10):2006	Required	Required		Resistance
Bulk Density, in (g/cc)	IS 13630 (Part 12):2006	NA	2.0, Min		> 2.1
mpact Resistance- Coefficient of Restitution	IS 13630 (Part 14):2006	Manufacturer to State	0.55, Min		0.7-0.85
Chemical Properties					
Resistance to Staining of Glazed Tiles		Min, Class 3	Class I, Min		Conforms
Resistance to Household Chemicals		Min, GA	Class AA, Min		Conforms
Resistance to Acids and Alkalis (with exception of hydrofluoric acid and its compounds)	IS 13630 (Part 8):2006	Test Method Available	Required, if agreed		Conforms

NOTE: Certain amount of Size and Shade variation is inherent in all ceramic products. Within the limits of printed material, the colors and aesthetics of the products correspond closely to those of illustrated products. Prospective customers are advised to inspect a sample of the tile before ordering and laying. At all points of time, the company liability is restricted to the purchase value of tiles.

Every effort has been made to ensure the accuracy of the information given. However, the company reserves the right to delete & change, any of the items, colors, sizes & technical specifications without any prior notice.



Whataspp : 87507 11111



www.orientbell.com

Missed Call: 87507 33333

Listed on BSE (530365) for 20+ years.

And also on NSE (ORIENTBELL).

CORPORATE OFFICE:

Iris House, 16 Business Centre, Nangal Raya, New Delhi – 110046, India Tel: +91-11-47119100 **REGISTERED OFFICE:**

8 Industrial Area, Sikandrabad – 203 205 (UP), India Tel: +91-5735-222-203 / 424, +91-8191004575 / 76













