



SKD FLOOR TILES COLLECTION **2020 600X1200 MM**




About OBL

Orient Bell Limited (OBL) is amongst the largest manufacturers of Wall & Floor Tiles. It's roots in the tile industry can be traced as early as 1977.

OBL has always been a pioneer in the Industry with a focus on customer-centric innovation. It was the first to manufacture ultra-vitrified tiles. For OBL, new product design & development is a continuous process. As a result it has an extensive range of tiles with various finishes & textures. It has 4 patent-pending technologies: Forever Tiles, GermFree Tiles, Cool Tiles & Life Tiles.

OBL has a chain of signature showrooms to display this extensive range of tiles. It is privileged to be associated with premier architects and construction agencies of the country. It counts most leading developers as well as government & public sector institutions as its customers.




















At OBL we believe in excellence. The ISO 9001:2015 accreditation for our quality control management systems reflects this quest for manufacturing products that meet international standards. In 2015 our Sikandarabad plant was awarded with prestigious ISI certification for its products.

As early as in May 2000, OBL was awarded the prestigious ISO 14001 certification by the internationally recognised BSI Management Systems, UK. Our manufacturing units are ISO 14001:2015 certified, the most complete and global expression for an environment friendly industrial company.

We believe in making great products in a safe, healthy and environment friendly way. We have been awarded OHSAS 18001 Certification for Health & Safety Standards. No waste water is ever discharged from our factory.

OBL won the "Certificate Of Merit" in 'National Energy Conservation Award' 2016 organised by Ministry of Power for saving Power and Fuel consumption.





INDEX

Statuario Marble				
600X1200 MM PGVT SUPER WHITE	01	Marble		Marble
600X1200 MM PGVT STATUARIO MARBLE	O1	600X1200 MM PGVT CALIFORNIA BEIGE	16	600X1200 MM RIVER WHITE
600X1200 MM PGVT CARARA MARBLE	01	600X1200 MM PGVT MIDTOWN LIGHT	16	600X1200 MM RIVER BROWN
600X1200 MM PGVT CARRARA NATURA	01	600X1200 MM PGVT REGAN IVORY	16	
600X1200 MM PGVT CALACATTA NATURA	O1	600X1200 MM PGVT ONYXO MARBLE	16	Marble-Granite
600X1200 MM PGVT STATUARIO NATURA	04	600X1200 MM PGVT ATLANTIS BEIGE	16	600X1200 MM CANTO ASH
		600X1200 MM PGVT ONYX CROSSCUT SMOKY	18	600X1200 MM CANTO COPPER
Travertine Marble		600X1200 MM PGVT ONYX BEIGE	18	600X1200 MM CANTO MULTI
600X1200 MM PGVT TRAVERTINE BROWN	05	600X1200 MM SATIN ONYX WHITE	18	600X1200 MM CANTO SILVER
600X1200 MM PGVT TRAVERTINE BEIGE	05	600X1200 MM PGVT MONACO BROWN	18	600X1200 MM CANTO WHITE
600X1200 MM PGVT TRAVERTINE CLASSIC BRONZE	05	600X1200 MM PGVT MONACO GREY	18	600X1200 MM STAR GOLD
600X1200 MM PGVT TRAVERTINE GREY	05	600X1200 MM PGVT MONACO CHOKO	18	600X1200 MM STAR ORANGE
600X1200 MM PGVT TRAVERTINO MARBLE	06	600X1200 MM PGVT BROWN STREAK BIANCO	20	600X1200 MM STAR SAND
600X1200 MM ROCKER TRAVERTINO GOLD	06	600X1200 MM PGVT BRECCIA BROWN	20	
600X1200 MM PGVT TRAVERTINE ONYX	06	600X1200 MM PGVT EMPERADOR BEIGE	20	
		600X1200 MM PGVT EMPERADOR GREY LIGHT	20	
		600X1200 MM PGVT VENEZIA CLASSIC GREY	20	
Super Gloss Marble		600X1200 MM PGVT VENEZIA CLASSIC BEIGE	20	
600X1200 MM SUPER GLOSS TAURUS BLACK MARBLE	08	600X1200 MM PGVT VENATO BEIGE	22	
600X1200 MM SUPER GLOSS BLACK MARBLE	08	600X1200 MM PGVT OMANI BEIGE MARBLE	22	
600X1200 MM SUPER GLOSS TORONTO MARBLE	08	600X1200 MM PGVT LIMESTONE SILVER GREY	22	
600X1200 MM SUPER GLOSS PORTORO GOLD MARBLE	08	600X1200 MM PGVT SOAPSTONE SMOKY	22	
600X1200 MM SUPER GLOSS MARQUINA BLACK	10	600X1200 MM PGVT SOAPSTONE BROWN	22	
600X1200 MM SUPER GLOSS MARMI GRAFITE	10	600X1200 MM ROCKER ANTIQUE MARBLE	24	
600X1200 MM SUPER GLOSS PIETRA GREY	10	600X1200 MM SATIN SOFTMARBO	24	
600X1200 MM SUPER GLOSS IGNEOUS ROCK	10	600X1200 MM SATIN CALACATTA MARBLE	24	
600X1200 MM SUPER GLOSS EMPERADOR DARK	10	600X1200 MM PGVT ONYX PEARL	25	
600X1200 MM SUPER GLOSS ARCTIC BLACK	10	600X1200 MM PGVT ARCTIC BLUE GRANITE	25	
600X1200 MM SUPER GLOSS EMPERADOR BROWN	12	600X1200 MM ROCKER CLASSIC MARFIL	25	
600X1200 MM SUPER GLOSS WAVE BLUE MARBLE	12	600X1200 MM DGVT CLASSIC MARFIL	25	
600X1200 MM SUPER GLOSS MARQUINA BLUE	12	600X1200 MM PGVT AUTHENTIC GREY LIGHT	26	
600X1200 MM SUPER GLOSS MONACO GREY	12	600X1200 MM PGVT AUTHENTIC IVORY	26	
		600X1200 MM PGVT STYLE STATUARIO	26	
Bookmatch Marble				
600x1200 MM PGVT ONYX MULTI MARBLE-A	14			
600x1200 MM PGVT ONYX MULTI MARBLE-B	14			

Code Description

DGVT-Digital Glazed Vitrified Tiles | PGVT- Polished Glazed Vitrified Tiles | OT-Orient Tile | PCG- Porcelain Gloss ODG-Orientbell Digital Gloss | ODM- Orientbell Digital Matte | ODP- Orientbell Digital Porcelain OEM- Orientbell Elevation Matte | DC-Double Charge | PDC-Printed Double Charge | PVT-Polished Vitrified Tiles R1-No Variation | R2-Slight Variation | R3-More Variation | R4- Most Variation F1-1 Face | F2-2 Face | F3-3 Face | F4-4 Face | F5-5 Face | F6-6 Face | F7-7 Face | F8-8 Face G1, G2, G3, G4, G5 (Grouping) are as per technical parameters



600X1200 MM | PGVT SUPER WHITE



600X1200 MM | PGVT STATUARIO MARBLE



600X1200 MM | PGVT CARARA MARBLE



600X1200 MM | PGVT CARRARA NATURA



600X1200 MM | PGVT CALACATTA NATURA





600X1200 MM | PGVT STATUARIO NATURA

The best of Statuario's are whitest white and have continuous veins running end to end of the slab. We built that into our tiles.





600X1200 MM | PGVT TRAVERTINE BROWN



600X1200 MM | PGVT TRAVERTINE CLASSIC BRONZE



600X1200 MM | PGVT TRAVERTINE BEIGE



600X1200 MM | PGVT TRAVERTINE GREY




600X1200 MM | PGVT TRAVERTINO MARBLE



600X1200 MM | ROCKER TRAVERTINO GOLD



600X1200 MM | PGVT TRAVERTINE ONYX








600X1200 MM | SUPER GLOSS TAURUS BLACK MARBLE




600X1200 MM | SUPER GLOSS TORONTO MARBLE



600X1200 MM | SUPER GLOSS BLACK MARBLE



600X1200 MM | SUPER GLOSS PORTORO GOLD MARBLE







Make your living room a space you enjoy coming together for quality time.



600X1200 MM | SUPER GLOSS EMPERADOR BROWN



600X1200 MM | SUPER GLOSS MARQUINA BLUE



600X1200 MM | SUPER GLOSS WAVE BLUE MARBLE



600X1200 MM | SUPER GLOSS MONACO GREY





Tile Faces representation




600x1200 MM | PGVT ONYX MULTI MARBLE-A




600x1200 MM | PGVT ONYX MULTI MARBLE-B

Bookmatch laying drawing




All shown tiles are Glossy






600X1200 MM | PGVT ATLANTIS BEIGE











600X1200 MM | PGVT OMANI BEIGE MARBLE



600X1200 MM | PGVT LIMESTONE SILVER GREY



600X1200 MM | PGVT SOAPSTONE SMOKY



600X1200 MM | PGVT SOAPSTONE BROWN



600X1200 MM | ROCKER ANTIQUE MARBLE



600X1200 MM | SATIN CALACATTA MARBLE



600X1200 MM | SATIN SOFTMARBO










600X1200 MM | ROCKER CLASSIC MARFIL

600X1200 MM | DGVT CLASSIC MARFIL





600X1200 MM | PGVT AUTHENTIC GREY LIGHT




600X1200 MM | PGVT AUTHENTIC IVORY



600X1200 MM | PGVT STYLE STATUARIO

600X1200 MM All shown tiles are Glossy









600X1200 MM | RIVER WHITE




All shown tiles are Glossy









INDEX

CEMENT

600X1200 MM | DGVT CEMENTUM CAMEL 33 600X1200 MM | DGVT CEMENTUM GRIS 33

Code Description


DGVT-Digital Glazed Vitrified Tiles | PCM- Porcelain Matte

ODM- Orientbell Digital Matte | ODP- Orientbell Digital Porcelain | OEM-Orientbell Elevation Matte

R1-No Variation | R2-Slight Variation | R3-More Variation | R4- Most Variation

F1-1 Face | F2-2 Face | F3-3 Face | F4-4 Face | F5-5 Face | F6-6 Face | F7-7 Face | F8-8 Face

G1, G2, G3, G4, G5 (Grouping) are as per technical parameters









600X1200 MM | DGVT CEMENTUM CAMEL



600X1200 MM | DGVT CEMENTUM GRIS



INDEX

WOOD

 600X1200 MM | TUSCANY WOOD BROWN
 36

 600X1200 MM | DGVT ECOWOOD MULTI
 36

 600X1200 MM | DGVT ARTICO WOOD BROWN
 36

Code Description

DGVT-Digital Glazed Vitrified Tiles | OT-Orient Tiles | PCM- Porcelain Matte

ODM- Orientbell Digital Matte | ODP- Orientbell Digital Porcelain | ODW-Orientbell Digital Wood

R1-No Variation | R2-Slight Variation | R3-More Variation | R4- Most Variation

F1-1 Face | F2-2 Face | F3-3 Face | F4-4 Face | F5-5 Face | F6-6 Face | F7-7 Face | F8-8 Face

G1, G2, G3, G4, G5 (Grouping) are as per technical parameters









600X1200 MM | TUSCANY WOOD BROWN



600X1200 MM | DGVT ARTICO WOOD BROWN



600X1200 MM | DGVT ECOWOOD MULTI



INDEX

STYLIZED

600X1200 MM | DGVT MOSAIC ART DÉCOR

20

Code Description

DGVT-Digital Glazed Vitrified Tiles | ODG-Orientbell Digital Glossy | ODP-Orientbell Digital Porcelain R1-No Variation | R2-Slight Variation | R3-More Variation | R4- Most Variation F1-1 Face | F2-2 Face | F3-3 Face | F4-4 Face | F5-5 Face | F6-6 Face | F7-7 Face | F8-8 Face G1, G2, G3, G4, G5 (Grouping) are as per technical parameters









600X1200 MM | DGVT MOSAIC ART DÉCOR

Packing Details					
Size	No. of Tiles	Covered Area Per Carton			
(In mm.)	Per Carton	(In Sq. Mtr.)	(In Sq. ft.)		
600X1200 (SKD)	2	1.44	15.5		

	Group B Ia as per IS	0 13006:2012 and Group B Ib as	per IS 15622:201 <i>7</i>			
Characteristics	Test Methods	Requirement as per ISO 13006 ≤ 0.5 Group B Ia	Requirement as per IS 15622:2017 0.08 <e 3%="" b="" group="" ib<="" th="" ≤=""><th colspan="2">OBL Norms</th></e>		OBL Norms	
Dimension & Surface Quality			Unrectified	Rectified		
Deviation in Length & Width		±0.6%	± 0.4%	± 0.1 %	± 0.1 %	
Deviation in Thickness		±5%	± 5	5.0 %	± 4 %	
Straightness of Sides	IS 10 (00 (D 1) 000 (±0.5%	± 0.3 %	± 0.1 %	± 0.1 %	
Rectangularity	IS 13630 (Part 1):2006	±0.5%	± 0.3 %	± 0.1 %	± 0.1 %	
Surface Flatness		±0.5%	± 0	0.5 %	± 0.2 %	
Surface Quality				iles should be isible defects	Conforms	
Physical Properties						
Water Absorption	IS 13630 (Part 2):2006	Avg ≤ 0.5, Individual max, 0.6	Avg 0.08 <e 3,<="" td="" ≤=""><td>Individual 3.3, Max</td><td>Avg ≤ 0.5, Individual max, 0.6</td></e>	Individual 3.3, Max	Avg ≤ 0.5, Individual max, 0.6	
Modulus of Rupture in [N/mm²]	IS 13630 (Part 6):2006	Minimum 35, Individual 32, Min	Avg 30, Individual 27, Min		Avg 38 Min, Individual 35, Min 😛	
Breaking Strength in N	IS 13630 (Part 6):2006	< 7.5 mm thickness: 700, Min ≥ 7.5 mm thickness: 1300, Min	< 7.5 mm thickness: 700, Min ≥ 7.5 mm thickness: 1100, Min		1500, Min	
Moisture Expansion in mm/m	IS 13630 (Part 3):2006	Declare Value	0.02, Max		< 0.02	
Scratch Hardness of Surface (Moh's Scale)	IS 13630 (Part 13):2006	NA	5, Min		5 to 8 Depending on Design/Surface	
Resistance to Surface Abrasion of Glazed Tiles (Class I to V)	IS 13630 (Part 11):2006	Test Method Available	Class II, Min		Class-III to Class-V Depending as per Design / Surface	
Co-efficient of Linear Thermal Expansion from Ambiant Temperature to 100°C	IS 13630 (Part 4):2006	Test Method Available	7x10°K², Max		Conforms	
Thermal Shock Resistance	IS 13630 (Part 5):2006	Test Method Available	10 cycles, Min		Passed	
Crazing Resistance	IS 13630 (Part 9):2006	Test Method Available	4 Cycles@7.5 bar, Min		4 Cycle @ 7.5 Bar Min	
Frost Resistance	IS 13630 (Part 10):2006	Required	Required		Resistance	
Bulk Density, in (g/cc)	IS 13630 (Part 12):2006	NA	2.0, Min		> 2.1	
Impact Resistance- Coefficient of Restitution	IS 13630 (Part 14):2006	Manufacturer to State	0.55, Min		0.7-0.85	
Chemical Properties						
Resistance to Staining of Glazed Tiles		Min, Class 3	Class	s I, Min	Conforms	
Resistance to Household Chemicals		Min, GA	Class	AA, Min	Conforms	
Resistance to Acids and Alkalis (with exception of hydrofluoric acid and its compounds)	IS 13630 (Part 8):2006	Test Method Available	Required, if agreed		Conforms	

Packing Details					
Size	No. of Tiles	Covered Area Per Carton			
(In mm.)	Per Carton	(In Sq. Mtr.)	(In Sq. ft.)		
600X1200 (West Zone)	2	1.44	15.5		

	2000/2000 000 /2000	S0 13006:2012 and Group B Ib as				
Characteristics	Test Methods	Requirement as per ISO 13006 ≤ 0.5 Group B Ia	Requirement as per IS 15622:2017 0.08 <e 3%="" b="" group="" ib<="" th="" ≤=""><th>OBL Norms</th><th></th></e>		OBL Norms	
Dimension & Surface Quality			Unrectified	Rectified		
Deviation in Length & Width		±0.6%	± 0.4%	± 0.1 %	± 0.1 %	
Deviation in Thickness		±5% ± 5.0 %		.0 %	± 4 %	
Straightness of Sides	IS 13630 (Part 1):2006	±0.5%	± 0.3 %	± 0.1 %	± 0.1 %	
Rectangularity	13 13030 (ran 1):2000	±0.5%	± 0.3 %	± 0.1 %	± 0.1 %	
Surface Flatness		±0.5%	± 0.5 % Min. 95 % tiles should be free from visible defects		± 0.2 %	96
Surface Quality		Min. 95 % tiles should be free from visible defects			Conforms	
Physical Properties						
Water Absorption	IS 13630 (Part 2):2006	Avg ≤ 0.5, Individual max, 0.6	Avg 0.08 <e 3,="" 3.3,="" individual="" max<="" td="" ≤=""><td>Avg ≤ 0.5, Individual max</td><td>, 0.6</td></e>		Avg ≤ 0.5, Individual max	, 0.6
Modulus of Rupture in [N/mm²]	IS 13630 (Part 6):2006	Minimum 35, Individual 32, Min	Avg 30, Individual 27, Min		Avg 38 Min, Individual 35	, Min 😀 🤇
Breaking Strength in N	IS 13630 (Part 6):2006	< 7.5 mm thickness: 700, Min ≥ 7.5 mm thickness: 1300, Min	< 7.5 mm thickness: 700, Min ≥ 7.5 mm thickness: 1100, Min		1 <i>5</i> 00, Min	96
Moisture Expansion in mm/m	IS 13630 (Part 3):2006	Declare Value	0.02, Max		< 0.02	
Scratch Hardness of Surface (Moh's Scale)	IS 13630 (Part 13):2006	NA	5, Min		5 to 8 Depending on Design/Surface	•
Resistance to Surface Abrasion of Glazed Tiles (Class I to V)	IS 13630 (Part 11):2006	Test Method Available	Class II, Min		Class-III to Class-V Deper as per Design / Surfa	
Co-efficient of Linear Thermal Expansion from Ambiant Temperature to 100°C	IS 13630 (Part 4):2006	Test Method Available	7x10°K¹, Max		Conforms	
Thermal Shock Resistance	IS 13630 (Part 5):2006	Test Method Available	10 cycles, Min		Passed	
Crazing Resistance	IS 13630 (Part 9):2006	Test Method Available	4 Cycles@7.5 bar, Min		4 Cycle @ 7.5 Bar M	lin 😃
Frost Resistance	IS 13630 (Part 10):2006	Required	Required		Resistance	
Bulk Density, in (g/cc)	IS 13630 (Part 12):2006	NA	2.0, Min		> 2.1	
Impact Resistance- Coefficient of Restitution	IS 13630 (Part 14):2006	Manufacturer to State	0.55, Min		0.7-0.85	
Chemical Properties						
Resistance to Staining of Glazed Tiles		Min, Class 3	Class I, Min		Conforms	
Resistance to Household Chemicals	IS 13630 (Part 8):2006	Min, GA	Class AA, Min Required, if agreed		Conforms	
Resistance to Acids and Alkalis (with exception of hydrofluoric acid and its compounds)		Test Method Available			Conforms	

TECHNICAL SPECIFICATIONS


Technical Specifications of Double Charge | Nano Tech Polished Vitrified Tiles | Printed Double Charge

Packing Details					
Size	No. of Tiles	Covered Area Per Carton			
(In mm.)	No. of Tiles Per Carton	(In Sq. Mtr.)	(In Sq. ft.)		
600X1200 (West Zone)	2	1.44	15.5		

As per Indian Standard (IS 15622:2017) Group B Ia					
Characteristics	Standard Test Method	IS 15622 Requirements	OBL Norms		
Dimension & Surface Quality					
Deviation in Length & Width		±0.1%	± 0.1 %		
Deviation in Thickness		±5.0%	± 3.0 %		
Straightness of Sides	- IS 13630 (Part 1):2006	±0.1%	± 0.1 %		
Squareness	13 13030 (1411 1):2000	±0.1%	± 0.1 %		
Surface Flatness		±0.50%	± 0.2 %		
Surface Quality		Min. 95 % tiles should be free from visible defects	Conforms		
Physical Properties					
Water Absorption %	IS 13630 (Part 2):2006	E ≤ 0.08	E ≤ 0.05		
Modulus of Rupture in [N/mm²]	IS 13630 (Part 6):2006	Avg≥35 N/mm²	>35 N/mm²		
Breaking Strength in N	IS 13630 (Part 6):2006	Min 1300	>1300 😊		
Scratching Resistance	IS 13630 (Part 13):2006	Min 5	≥ 5		
Deep Abrasion	IS 13630 (Part 12):2006	140 Max	100 Max 😊		
Chemical Properties					
Resistance to Staining	IS 13630 (Part 8):2006	Min, Class 2	Conforms		
Resistance to Household Chemicals	- 13 13030 (run 6):2000	Min, Class AA	Conforms		
Thermal Specifications					
Thermal Shock Resistance	IS 13630 (Part 5):2006	Min 10 Cycles	Conforms		
Thermal Expansion	IS 13630 (Part 4):2006	Max 6X10° at 100° c (K ⁻¹)	Conforms		
Frost Resistance	IS 13630 (Part 10):2006	10 Cycles pass	Conforms		
Impact Resistance	IS 13630 (Part 14):2006	0.55 minimum	Conforms		
Bulk Density (gm/cc)	IS 13630 (Part 2):2006	Min 2.2	Conforms		

NOTE: Certain amount of Size and Shade variation is inherent in all ceramic products. Within the limits of printed material, the colors and aesthetics of the products correspond closely to those of illustrated products. Prospective customers are advised to inspect a sample of the tile before ordering and laying. At all points of time, the company liability is restricted to the purchase value of tiles.

Every effort has been made to ensure the accuracy of the information given. However, the company reserves the right to delete & change, any of the items, colors, sizes & technical specifications without any prior notice.



A Network of 2500+ Channel Partners

- Franchise Owned Boutiques
- Channel Partners
- Company Owned Boutiques



ORIENT BELL TILE BOUTIQUE

CHANDIGARH

SCO - 6, First Floor, Sector 7-C, Madhya Marg, Chandigarh-160 019, Tel.: +91 172 4624 342

CHENNAI

New No: 85, Old No: 30, Maharaja Tower, 2nd Floor, 1st Avenue, Ashok Nagar, (Above Kotak Mahindra Bank), Chennai-600 083, Tel.: +91 44 4213 8687

COCHIN

"SURYA GAYATRI", Building No. 32/8, B3, Puthiya Road, New Junction, (Opposite Holiday Inn Hotel) Ernakulam By Pass Road, Cochin-682 031, Tel.: +91 9745768058

COIMBATORE

11, 1st Floor, Venkata Samy Road (East), R.S. Puram, Coimbatore-641 002, Tel.: +91 8979941666

DEHRADUN

Duggal Complex (Near Kamla Palace Hotel), GMS Road, Dehradun-248 001, Tel.: +91 9719701064

KOLKATA

8/1, Burdwan Road, Alipore, Kolkata-700 027, Tel.: +91 33 4068 4046/7

LUCKNOW

Raj Rani Apartment, Ground Floor, Near Beej Nigam, Badhshah Nagar Railway Station, Lucknow-226 006, Tel.: +91 99847 86404

NEW DELHI

M-47, GK-II, M Block, New Delhi-1100 048, Tel.: +91 11 4068 7468/69

PUNE

Shop No. 3 and 4, A Tower Vega Centre, C.T.S No. 710, Final Plot No. 401/1, Shankarasheth Road, Gultekdi, Swargate, Pune-411 037 Tel.: +91 73910 72247

VADODRA DISPLAY CENTRE

78-79, 2nd Floor, Surya Kiran Complex, Beside Banker Heart Institute, Old Padra Road, Vadodara-390007, Gujarat Tel.: +91 98254 14113





Listed on BSE (530365) for 20+ years. And also on NSE (ORIENTBELL).

CORPORATE OFFICE:

Iris House, 16 Business Centre, Nangal Raya, New Delhi – 110046, India Tel: +91-11-47119100 REGISTERED OFFICE:

8 Industrial Area, Sikandrabad – 203 205 (UP), India Tel: +91-5735-222-203 / 424, +91-8191004575 / 76











